


**STANDARD NOTES:**

1. UNLESS OTHERWISE DIRECTED BY THE WPCA OR ITS TECHNICAL CONSULTANT, MINIMUM PITCH FOR 6" SERVICE LATERALS SHALL BE 1/4" PER FOOT.
2. PROPOSED LOCATIONS OF SERVICE LATERALS TO BE COORDINATED IN THE FIELD WITH THE WPCA OR ITS TECHNICAL CONSULTANT.
3. IF ROCK IS PRESENT, IT SHALL BE EXCAVATED AT LEAST 10- FEET BEYOND THE END OF THE STUB WITHIN THE RIGHT OF WAY OR SEWER EASEMENT.
4. REFER TO SECTION 02515 FOR ADDITIONAL REQUIREMENTS ASSOCIATED WITH GRAVITY SEWER SERVICES.
5. CLEANOUTS SHALL ONLY BE USED IN CONJUNCTION WITH GRAVITY SEWER SERVICES IN THOSE LOCATIONS DIRECTED BY THE WPCA OR ITS TECHNICAL CONSULTANT.
6. IF DIRECTED BY WPCA OR ITS TECHNICAL CONSULTANT, MARKER POST CAN BE LEFT 6" ABOVE FINISHED GRADE.



Water Pollution Control Authority  
Town of Canton

4 Market Street  
P.O. Box 168  
Collinsville, Connecticut 06022

**SEWER CONSTRUCTION DETAIL**

GRAVITY SANITARY SEWER  
SERVICE LATERAL  
WITH CLEANOUT

NO SCALE

LATEST REVISION: 2/07

NO. 010